

## RXO2520C

The RXO2520C is a Crystal Oscillator (XO) in a compact 2.5 x 2.0 mm footprint, designed with a CMOS output for reliable clock generation. Its small form factor makes it an ideal choice for space-constrained Surface-Mount Device (SMD) applications. It delivers  $\leq 1$  ps RMS phase jitter (measured from a 12 kHz to 20 MHz offset). For applications requiring even lower jitter, an option with typical jitter as low as 50 fs is available upon request.

This device supports a wide range of industry-standard frequencies from 0.5 to 133 MHz. It provides various frequency stability options across a wide operating temperature range, considering factors such as initial frequency calibration, supply and load variations, and one-year ageing effects. The RXO2520C is well-suited for diverse applications in consumer electronics, computing, networking, data centres, industries, and more.

### Features

- Frequency (Fn): 0.5 to 133 MHz
- Output: CMOS
- Wide frequency range
- Operating temperature: -40 to 125°C
- Low phase noise and RMS jitter

### Applications

- Consumer electronics
- Computing, Networking
- Processing, Data storage
- Data centre
- Medical, Industrial

2.5 x 2.0 x 0.8 mm



### Standard Specifications

Parameter	Min.	Typ.	Max.	Unit	Test Condition / Description
Nominal frequency (Fn)	0.5		133	MHz	
Temperature range	-40		85 ~ 125	°C	
Frequency stability			$\pm 25 \sim \pm 50$	ppm	Including frequency calibration, operating temperature range, supply and load variations, and 1 year ageing at 25°C
Supply voltage (V <sub>DD</sub> )		1.8/2.5/3.3		V	With a tolerance of $\pm 5\%$
Supply current				mA	
	$\leq 20$ MHz		6		
	$\leq 40$ MHz		7		
	$\leq 60$ MHz		9		
	$\leq 133$ MHz		18		
RMS phase jitter			1	ps	Integrated from 12kHz to 20MHz

### Model Outline and Recommended Pad Layout

**RECOMMENDED PAD LAYOUT**

– TOP VIEW

Pin	Connections
1*	Enable/Disable (E/D)
2	GND
3*	Output
4	V <sub>DD</sub>

E/D function	Pin 1	Pin 4
	High or Open	Operating
Low	High Impedance	

**NOTE:** Outline unit is mm.